



TECHNICAL BULLETIN

Professional Foam-Cut Compound

Meguiar's® Foam-Cut Compound features exclusive, buffered super-micro abrasive technology delivering ultra-fast reliable sanding mark removal, while leaving a high gloss low swirl finish on all freshly painted surfaces.

Part #:	M10132 - 32 oz M10101 – 1 gallon
Packaging:	32 Oz Compound- 6 per case 1 Gallon Compound- 4 per case
Features:	<ul style="list-style-type: none">• Exclusive, Buffered Super-Micro Abrasive Technology• Safe on all fresh paint finishes, including Scratch Resistant Coatings (SRC)• Performance matched to Meguiar's Soft Buff Foam Compounding Pad (W6006)• Minimal pad sling and fast wipe off for excellent clean-up performance• Globally VOC compliant formula
pH:	8.4 – 8.9
Paintable:	Yes
Dilution:	RTU (Ready to use)
Application Method:	Rotary
Directions:	Shake Well. For best results, prime dry pad by directly applying Foam-Cut Compound to the pad face. Work surface at approximately 900-1500 rpm using moderate downward pressure until sanding marks are removed. Re-apply if necessary. Clean pad frequently using Meguiar's Pad Conditioner Brush (WPCB). To deep clean buffing pad, use Meguiar's Pad Washer (WPW). Wipe off final residue using Meguiar's Ultimate Wipe® Detailing Cloth (M9910). For maximum luster, complete process using your favorite Meguiar's polish using a Soft Buff® 2.0 Foam Finishing Pad (W9207 or W9204).
Associated Products:	<ul style="list-style-type: none">• Meguiar's® Soft-Buff™ Compounding Pad (W6006)• Meguiar's® Easy-Buff Backing Plate (W6114MM / W6116MM)• Meguiar's® Unigrit™ 1500 Sanding Discs (S31500 / S61500)• Meguiar's® Unigrit™ 3000 Finishing Discs (S3F3000 / S6F3000)• Meguiar's® Unigrit™ Foam Interface Pad (S3FIS / S6FI)• Meguiar's® Professional Backing Pad (S6BP)• Meguiar's® Ultimate Wipe™ Microfiber Towel (M9910)
Health rating:	Health: 2 Fire: 2 Reactivity: 0 Specific Hazard: N/A